

breneco



CODE	TYPE	Ah	A (-18°C) EN7,5V10"	DIMENSIONS (mm)			LAYOUT	TERMINAL TYPE	HOLD DOWN
				L	W	H			
AGM-PowerX									
601 060 680	AGM-B2	60	680	242	175	190		STD	B3
601 070 760	AGM-B3	70	760	275	175	190		STD	B3
601 080 800	AGM-B4	80	800	310	175	190		STD	B3
601 095 850	AGM-B5	95	850	353	175	190		STD	B3
601 105 950	AGM-B6	105	950	393	175	190		STD	B3
EFB-PowerX									
602 050 500	EFB-B1	55	500	207	175	190		STD	B3
602 060 570	EFB-B2	60	570	242	175	190		STD	B3
602 065 650	EFB-B3	65	650	275	175	175		STD	B3
602 072 720	EFB-B4	72	720	275	175	190		STD	B3
602 075 730	EFB-B5	75	730	310	175	175		STD	B3
602 080 770	EFB-B6	80	770	310	175	190		STD	B3
602 100 850	EFB-B7	100	850	353	175	190		STD	B3
S-PowerX LD									
604 047 450	S47-LD	47	450	207	175	175		STD	B3
604 062 590	S62-LD	62	590	242	175	175		STD	B3
604 072 680	S72-LD	72	680	275	175	175		STD	B3
604 082 740	S82-LD	82	740	310	175	175		STD	B3
604 092 800	S92-LD	92	800	353	175	175		STD	B3

TERMINAL TYPE : STD=Standard, SM=Small

CODE	TYPE	Ah	A (-18°C) EN7,5V10"	DIMENSIONS (mm)			LAYOUT	TERMINAL TYPE	HOLD DOWN
				L	W	H			
S-PowerX									
603 044 420	S44	44	420	175	175	190		STD	B3
603 050 450	S50	50	450	207	175	190		STD	B3
603 055 500	S55	55	500	207	175	190		STD	B3
613 055 500	S55L	55	500	207	175	190		STD	B3
603 062 590	S62	62	590	242	175	190		STD	B3
613 062 590	S62L	62	590	242	175	190		STD	B3
603 074 680	S74	74	680	275	175	190		STD	B3
613 074 680	S74L	74	680	275	175	190		STD	B3
603 080 720	S80	80	720	275	175	190		STD	B3
603 100 800	S100	100	800	310	175	190		STD	B3
613 100 800	S100L	100	800	310	175	190		STD	B3
603 100 830	S100S	100	830	353	175	190		STD	B3
S-PowerX JS									
605 037 330	JS37	37	330	187	127	225		SM	B0
615 037 330	JS37L	37	330	187	127	225		SM	B0
605 045 360	JS45	45	360	237	127	225		SM	B0
615 045 360	JS45L	45	360	237	127	225		SM	B0
605 060 490	JS60	60	490	230	170	225		STD	B0
615 060 490	JS60L	60	490	230	170	225		STD	B0
605 095 760	JS95	95	760	303	175	225		STD	B6
615 095 760	JS95L	95	760	303	175	225		STD	B6
S-PowerX UHD									
606 150 085	S150-UHD	150	850	510	189	223		STD	B0
606 180 105	S180-UHD	180	1050	513	223	223		STD	B0
606 230 125	S230-UHD	230	1250	518	273	240		STD	B0
S-PowerX HD									
617 135 085	S135-HDL	135	850	510	189	223		STD	B0
617 150 090	S150-HDL	150	900	510	189	223		STD	B0
617 150 100	S150-HDML	150	1000	510	175	225		STD	B3
607 150 090	S150-HD	150	900	513	223	223		STD	B3
617 150 190	S150-HDBL	150	900	513	223	223		STD	B0
607 180 100	S180-HD	180	1000	513	223	223		STD	B3
617 180 100	S180-HDL	180	1000	513	223	223		STD	B0
607 200 110	S200-HD	200	1100	513	223	223		STD	B3
617 200 110	S200-HDL	200	1100	513	223	223		STD	B0
607 225 120	S225-HD	225	1200	518	273	240		STD	B0
617 225 120	S225-HDL	225	1200	518	273	240		STD	B0

